

# Scan Box - bis 50 VM / bis 150 VM

Technische Spezifikationen



**1 U Rackmount Network Appliance Platform with LGA 1151 Socket Intel® Core™ Intel® C246 und 26 LAN**

## Features

- LGA 1151 socket 9th/8th gen Intel® Core™ /Xeon® E-2200 processor(Coffee Lake)
- 4 DDR4-2666 U-DIMM for up to 64GB of memory
- max. up to twenty-six 10/100/1000 Mbps Ethernet ports
- 2 expandable LAN modules supporting 1 GbE/10 GbE/25 GbE/40 GbE/Fiber/Copper/Bypass
- Supports 1U redundant power supply for optional
- Supports IPMI/TPM for optional
- Suitable for network security, cloud computing and data centers applications

## Specifications

### System

CPU	LGA 1151, 3,00 GHz i5-8500
Chipset	Intel® C246
Memory	* DDR4-2666 U-DIMM, 32 GB (bis 50 VM) 64 GB (bis 150 VM) * non-buffer non-ECC/ECC memory
Storage	* 1 x mSATA256 GB * 1 x 3.5 SATA SSD 1 TB
Network Interface	* C246: 8 x 10/100/1000 Mbps (Intel® i210) * 2 x LAN module (optional), max. up to 26 LANs
I/O	* 1 x RS-232 (RJ-type) * 2 x USB 3.0 * 8 x RJ-45
Power Supply	* 400W ATX power supply

## Mechanical/Environmental

Form Factor	1U rackmount
Operating Temp.	* 0°C to +45°C * (400W ATX power supply) * 0°C to +40°C * (400W 1U redundant power supply)
Humidity	* 10% to 95% RH, non-condensing
Chassis Material	* Steel
Dimensions	* 44 mm (H) x 430 mm (W) x 450 mm (D)
Weight	* 6 kg
Certifications	* FCC class A, CE class A

\*Abweichungen | Änderungen bzgl. technischem Fortschritt vorbehalten!

# Scan Box - bis 250 VM

Technische Spezifikationen



**1 U Rackmount Network Appliance Platform with LGA 3647 Socket Intel® Core™ Intel® Xeon® Scalable Processor (Cascade Lake/Skylake), Intel® C621 (Purley) and up to 34 LAN**

## Features

- LGA 3647 socket Intel® Xeon® Scalable Processor
- 6 DDR4-2400 R-DIMM for up to 192 GB of memory
- max. up to thirty-four 10/100/1000 Mbps Ethernet ports
- 4 expandable LAN modules supporting 1 GbE/10 GbE/25 GbE/40 GbE/Fiber/Copper/Bypass
- Supports 1U redundant power supply
- Supports IPMI/TPM (onboard) for optional
- High computing power for SDN, NGFW, IDS, IPS and UTM applications

## Specifications

### System

CPU	LGA 3647, socket Intel® Xeon® Silver 4112
Chipset	Intel® C621
Memory	* DDR4 2400 R DIMM, 128 GB * non-buffer non-ECC/ECC memory
Storage	* 1 x 2,5 SATA SSD 2 TB * 1 x mSATA 256 GB
Network Interface	* 2 x 10/100/1000 Mbps Ethernet (Intel® i210) * 3 x LAN module (optional), max. up to 34 LAN ports
I/O	* 1 x RS-232 (RJ-type) * 2 x USB 3.0 * 2 x RJ-45
Power Supply	* 400W 1U power supply

### Mechanical/Environmental

Form Factor	1U rackmount
Operating Temp.	* 0°C to +45°C
Humidity	* 10% to 95% RH, non-condensing
Chassis Material	* Steel
Dimensions	* 44 mm (H) x 430 mm (W) x 561 mm (D)
Weight	* 8 kg
Certifications	* FCC class A, CE class A

\*Abweichungen | Änderungen bzgl. technischem Fortschritt vorbehalten!